HP550-S

LED Hotplate

Features:

- LED display shows temperature
- Max. temperature to 550°C.
- Separate safety circuits with fixed safety temperature of 580°C
- External temperature control is possible by connecting the temperature sensor(PT 1000) with an accuracy at ± 0.5 °C
- Glass ceramic work plate provides excellent chemical-resistant performance and most efficient heat transferer
- The "HOT" warning will flash when the work plate temperature is above 50°C even the hotplate is turned off



Wide range of accessory



Chemical resistance



Overheating protection



"HOT" warning to prevent burns



Specifications

Work plate Dimension [W x D]
Work plate material
Power
Voltage Frequency
Heating Power
heating position
Heating temperature range
Control accuracy of work plate
Safety temperature
Temperature display
Temperature display accuracy
External temperature sensor
Heating warning
Protection class
Dimension [W x D x H]
Weight
Permissible ambient temperature and humidity

HP550-S

184x184mm (7 inch)
Glass ceramic
1010W
100~120/200~240V,50/60Hz
1000W
1
Room temp550°C,increment 5°C
±10°C
580℃
led
±1°C
PT1000(±0.5°C)
50°C
IP2X
215x360x112mm
4.5kg
5~40°C 80%

ติดต่อบริษัท นีโอนิคส์ จำกัด Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz